



MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LOCTITE 771 NICKEL ANTI-SEIZE

Proper Shipping Name: None allocated

Product code(s): 472902, 267237, 641488

Part Number(s): 28182A (28g), 33630 (28g), 39163 (500g)

Use: High temperature anti-seize compound

Supplier: HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996
TECHNOLOGIES
135-141 Canterbury Road, Kilsyth, Victoria, 3137. Tel: (03) 9724 6444
24 HOUR EMERGENCY CONTACT NUMBER Tel: 1800 032 379

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:
Hazardous according to the criteria of ASCC. This material has been classified as Harmful (Xn) and Irritant (Xi).

Risk phrase(s):
R36/38 Irritating to eyes and skin.
R40 Limited evidence of a carcinogenic effect.
R43 May cause sensitisation by skin contact.

Safety phrase(s):
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28 After contact with skin, wash immediately with plenty of soap suds.
S37/39 Wear suitable gloves and eye/face protection.
S46 If swallowed, seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:
Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SUSDP POISON SCHEDULE: None allocated

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Petroleum hydrocarbons		> 60% w/w
Nickel	[7440-02-0]	10-20% w/w
Graphite		10-20%w/w
Petroleum sulphonate		<10%w/w
Aluminum		<5%w/w

SECTION 4. FIRST AID MEASURES

Ingestion: If swallowed, **do not induce** vomiting. Seek medical attention or contact a Poisons Information Centre (Phone 13 11 26).

DATE OF ISSUE: 26.05.08 **REVISION OF:** May 2003 **IDH NO: -**
Page 1 of 4 **PRODUCT NAME:** LOCTITE 771 NICKEL ANTI-SEIZE



MATERIAL SAFETY DATA SHEET

Skin: Remove contaminated clothing and wash affected areas with plenty of soap and water. If irritation occurs, seek medical attention.

Eyes: Hold eyes open and flush with water for at least 15 minutes. Seek medical attention or contact a Poisons Information Centre (Phone 13 11 26).

Inhalation: If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.

Advice to doctor: Treat symptomatically.

First Aid facilities: Eye wash and normal washroom facilities

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide, foam, dry chemical.

Hazards from combustion products: Combustible paste. In a fire, it will emit oxides of carbon, oxide of sulphur and irritating fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, then fire-fighters should wear full protective clothing and self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear impervious gloves, chemical goggles and waterproof boots. Contain and collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Use a non-flammable solvent or detergent and excess water to clean up areas in contact with spilled material. Do not contaminate watercourse. Dispose of residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Wear neoprene gloves and safety glasses.

Storage: Store indoors at ambient temperatures. Keep containers sealed when not in use. Protect from physical damage.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards: TWA : 1 mg/m³ as Nickel
5 mg/m³ as aluminium (fumes)

Engineering controls: If processing vapours/dusts are produced, use a local mechanical exhaust system.

Personal protective equipment: Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, safety footwear, neoprene gloves and chemical splash goggles. Use in a well ventilated area. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance: Dark grey paste
Specific gravity: 1.20
Solubility: Insoluble in water

DATE OF ISSUE: 26.05.08
Page 2 of 4

REVISION OF: May 2003
PRODUCT NAME:

IDH NO: -
LOCTITE 771 NICKEL ANTI-SEIZE



MATERIAL SAFETY DATA SHEET

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Avoid sources of ignition.

Incompatible materials: Keep away from phosphorus, alcohols, sulphur, selenium and oxidising agents.

Hazardous decomposition products: When heated to decomposition, it will emit oxides of carbon, oxides of sulphur and irritating fumes.

Other reactions: Nickel will react slowly with hydrochloric acid, sulphuric acid and nitric acid. Under certain conditions it may release hydrogen gas, a flammable gas.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute:

Ingestion: If swallowed, this product will cause irritation to the mouth, throat and digestive tract.

Skin: Contact with the skin may cause irritation. This product may cause skin sensitisation in susceptible individuals.

Eyes: Contact with the eyes can cause irritation.

Inhalation: Inhalation of vapour from the heated product may cause irritation to the nose and throat.

Chronic: Repeated skin contact may lead to dermatitis. This product contains nickel, for which there is limited evidence of a carcinogenic effect (category 3). Repeated inhalation of graphite dusts may cause pulmonary disease.

Exposure to free respirable nickel or graphite dust is not anticipated during normal use of this product. However, grinding or machining of coated parts may release dust/fumes. Under such circumstances, wear an approved dust/mist respirator.

Toxicity information: None available.

SECTION 12. ECOLOGICAL INFORMATION

Do not contaminate waterways and soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of this material should be undertaken by a registered chemical disposal company. Empty containers should be cleaned by a registered contractor and then recycled or disposed of at an approved land waste site.

SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated



MATERIAL SAFETY DATA SHEET

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

ASCC - Australian Safety and Compensation Council

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.