



MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LOCTITE SILVER GRADE ANTI-SEIZE LUBRICANT

Proper Shipping Name: None allocated

Product code(s): 199012, 471321, 552091, 471322, 471319, 235014

Part Number(s): 76732 (236ml), 76741 (250g), 76769 (500g), 76731 (5kg), 76785 (10kg), 76779 (194kg)

Use: Anti-seize compound

Supplier: HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996
TECHNOLOGIES
135-141 Canterbury Road, Kilsyth, Victoria, 3137. Tel: (03) 9724 6444
24 HOUR EMERGENCY CONTACT NUMBER Tel: 1800 032 379

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of ASCC. This material has been classified as Irritant (Xi).

Risk phrase(s):

R36/38 Irritating to eyes and skin.

Safety phrase(s):

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of soap suds.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SUSDP POISON SCHEDULE: None allocated

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

| CHEMICAL ENTITY | CAS NO. | PROPORTION |
|------------------------|-------------|-------------|
| Petroleum hydrocarbons | | 30- 60% w/w |
| Graphite | [7782-42-5] | 10-30%w/w |
| Calcium oxide | [1305-78-8] | 10-30%w/w |
| Aluminium | | <10%w/w |

SECTION 4. FIRST AID MEASURES

Ingestion: If swallowed, **do not induce** vomiting. Seek medical attention or contact a Poisons Information Centre (Phone 13 11 26).

Skin: Remove contaminated clothing and wash affected areas with plenty of soap and water. If irritation occurs, seek medical attention.

Eyes: Hold eyes open and flush with water for at least 15 minutes. Seek medical attention or contact a Poisons Information Centre (Phone 13 11 26).



MATERIAL SAFETY DATA SHEET

Inhalation: If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.

Advice to doctor: Treat symptomatically.

First Aid facilities: Eye wash and normal washroom facilities

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide, foam, dry chemical.

Hazards from combustion products: Combustible paste. In a fire, it will emit oxides of carbon and irritating fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, then fire-fighters should wear full protective clothing and self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear impervious gloves, chemical goggles and waterproof boots. Contain and collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Use a non-flammable solvent or detergent and excess water to clean up areas in contact with spilled material. Do not contaminate watercourse. Dispose of residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Wear neoprene gloves and safety goggles.

Storage: Store indoors at ambient temperatures. Keep containers sealed when not in use. Protect from physical damage.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards: TWA : 5 mg/m³ as aluminium (fumes)
2 mg/m³ as calcium oxide

Engineering controls: If processing vapours or dusts are produced, use a local mechanical exhaust system.

Personal protective equipment: Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, safety footwear, neoprene gloves and chemical splash goggles. Use in a well ventilated area. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance: Silver coloured smooth paste
Specific gravity: 1.25
Solubility: Insoluble in water
Flash point: >150°C

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Avoid sources of ignitions.

Incompatible materials: Keep away from strong bases, alcohols and oxidising agents.

Hazardous decomposition products: When heated to decomposition, it will emit oxides of carbon and irritating fumes.

DATE OF ISSUE: 26.05.08
Page 2 of 4

REVISION OF: May 2003
PRODUCT NAME: LOCTITE SILVER GRADE ANTI-SEIZE LUBRICANT

IDH NO: -



MATERIAL SAFETY DATA SHEET

Hazardous reactions: No polymerisation will occur.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute:

Ingestion: If swallowed, this product will cause irritation to the mouth, throat and digestive tract.

Skin: Contact with the skin may cause irritation.

Eyes: Contact with the eyes can cause irritation.

Inhalation: Inhalation of vapour from the heated product may cause irritation to the nose and throat.

Chronic: Repeated skin contact may lead to dermatitis. Repeated inhalation of graphite dusts may cause pulmonary disease. Exposure to free graphite dust is not anticipated during normal use of this product. However, grinding or machining of coated parts may release dust/fumes. Under such circumstances wear an approved respirator.

Toxicity information: None available.

SECTION 12. ECOLOGICAL INFORMATION

Do not contaminate waterways and soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of this material should be undertaken by a registered chemical disposal company. Empty containers should be cleaned by a registered contractor and then recycled or disposed of at an approved land waste site.

SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

ASCC - Australian Safety and Compensation Council

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

TWA – Time weighted average

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes

DATE OF ISSUE: 26.05.08
Page 3 of 4

REVISION OF: May 2003
PRODUCT NAME: LOCTITE SILVER GRADE ANTI-SEIZE LUBRICANT

IDH NO: -



MATERIAL SAFETY DATA SHEET

no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.