

Dow Corning Australia Pty Ltd

Material Safety Data Sheet

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product Details

Product Name: MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT
Other Name: Silicone grease.
Company Product Code: 01889770
Proper Shipping Name: Not applicable.
Recommended Use: Lubricant

1.2 Company Details

Manufacturer/Supplier: Dow Corning Australia Pty Ltd
Address: 3 Innovation Road, North Ryde, NSW 2113, Australia
Telephone Number: 1300-360-732
Emergency Telephone Number: 1300-360-732

2. HAZARD IDENTIFICATION

- 2.1 Hazard Classification:** Non-Hazardous Substance. Non-Dangerous Goods.
2.2 Risk Phrase(s): Not hazardous.
2.3 Safety Phrase(s): Avoid contact with skin and eyes.
 In case of fire and/or explosion do not breathe fumes.
 Use only in well-ventilated areas.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion %</u>
----------------------	-------------------	---------------------

Ingredients determined not to be hazardous to 100%

4. FIRST AID MEASURES

4.1 First Aid Measures:

Ingestion: Get medical attention.
Eye: Immediately flush with water.
Skin: No first aid should be needed.
Inhalation: No first aid should be needed.

4.2 Medical Attention and Special Treatment Needed:

First Aid Facilities: None should be required.
Comments: Treat symptomatically.
Note to physicians: Treat Symptomatically. For further information, the Medical Practitioner should contact Dow Corning Australia Pty Ltd.

Dow Corning Australia Pty Ltd

Material Safety Data Sheet

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT

5. FIRE FIGHTING MEASURES

- | | |
|--|---|
| 5.1 Suitable Extinguishing Media: | On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers. |
| 5.2 Hazards From Combustion Products: | Silicon dioxide. Metal oxides. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. |
| 5.3 Precautions For Fire Fighters and Special Protective Equipment: | Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. |
| 5.4 Hazchem Code: | Not applicable. |

6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| 6.1 Emergency Procedures: | Not applicable. |
| 6.2 Methods and Materials for Containment and Clean Up Procedures: | Observe all personal protective equipment recommendations described in this MSDS. If diked material can be pumped, store recovered material in appropriate container. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which laws and regulations are applicable. |

7. HANDLING AND STORAGE

- | | |
|---|---|
| 7.1 Precautions for Safe Handling: | Use with adequate ventilation. Traces of benzene (carcinogen) may form if heated in air above 445 degrees F (230 degrees C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Avoid eye contact. Do not take internally. Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking. |
| 7.2 Conditions for Safe Storage: | Use reasonable care and store away from oxidizing materials. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Standards:

Ingredients

None known.

Exposure Limits

Dow Corning Australia Pty Ltd
Material Safety Data Sheet**MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT****8.2 Engineering Controls:**

Local Ventilation: None should be needed.
General Ventilation: Recommended.

8.3 Personal Protective Equipment:

Respiratory: No respiratory protection should be needed.
Suitable Respirator: None should be needed.
Hand: No special protection needed.
Eye: Use proper protection - safety glasses as a minimum.
Skin: Washing at mealtime and end of shift is adequate.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

- 9.1 Physical Form:** Grease
9.2 Colour: Pink
9.3 Odour: Slight odor
9.4 pH: Not determined.
9.5 Vapour Pressure @ 25°C: Not determined.
9.6 Vapour Density (air=1): Not determined.
9.7 Boiling Point: Not determined.
9.8 Melting Point: Not determined.
9.9 Solubility in Water: Not determined.
9.10 Specific Gravity @ 25°C: 1.1
9.11 Flash Point: > 101.1 °C (Closed Cup)
9.12 Upper Flammability Limit: Not determined.
9.13 Lower Flammability Limit: Not determined.
9.14 Autoignition Temperature: Not determined.
9.15 Viscosity: Not determined.

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

- 10.1 Chemical Stability:** Stable.
10.2 Conditions to avoid: None.
10.3 Incompatible Materials: Can react with strong oxidising agents.
10.4 Hazardous Decomposition Products: Silicon dioxide. Metal oxides. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

Dow Corning Australia Pty Ltd
Material Safety Data Sheet

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT

10.5 Hazardous Reactions : Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

11.1 Possible Routes of Exposure Inhalation Skin Contact Ingestion

11.2 Possible Health Effects:

Acute

Ingestion: Low ingestion hazard in normal use.
Eye: Direct contact may cause temporary redness and discomfort.
Skin: No significant irritation expected from a single short-term exposure.
Inhalation: No significant effects expected from a single short-term exposure.

Chronic

Ingestion: Repeated ingestion or swallowing large amounts may injure internally.
Skin: No known applicable information.
Inhalation: No known applicable information.
Other Health Hazard Information: No known applicable information.

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

12. ECOLOGICAL INFORMATION

12.1 Environmental Fate and Distribution:

Solid material, insoluble in water. No adverse effects are predicted.

12.2 Ecotoxicity:

No adverse effects on aquatic organisms are predicted.

Bioaccumulation: No bioaccumulation potential.

12.3 Fate and Effects in Waste Water Treatment Plants:

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDERATIONS

13.1 Disposal Method: Dispose of in accordance with local regulations.

13.2 Special Precautions for Landfill or Incineration: None known.

Dow Corning Australia Pty Ltd

Material Safety Data Sheet

MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, LIGHT

14. TRANSPORT INFORMATION

- | | |
|--------------------------------------|----------------------------------|
| 14.1 UN No.: | Not applicable. |
| 14.2 Proper Shipping Name: | Not applicable. |
| 14.3 Class: | Not applicable. |
| 14.4 Packing Group: | Not applicable. |
| 14.5 Hazchem Code: | Not applicable. |
| 14.6 Sea transport (IMDG) | Not subject to IMDG code. |
| 14.7 Air Transport (IATA-DGR) | Not subject to IATA regulations. |

15. REGULATORY INFORMATION

- | | |
|--|---|
| 15.1 SUSDP Poisons Schedule Number: | None allocated. |
| 15.2 Prohibition/Licensing Requirements: | There are no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation. |
| 15.3 Industrial Chemicals (Notification and Assessment) Act 1989: | All ingredients listed or exempt. |
| 15.4 Chemical Inventories: | |
| EINECS: | All ingredients listed or exempt. |
| IECSC: | All ingredients listed or exempt. |
| DSL: | All chemical substances in this material are included on or exempted from the DSL. |
| TSCA: | All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances. |
| MITI: | Consult your local Dow Corning office. |
| PICCS: | Not determined. |
| KECL: | One or more ingredients are not listed or exempt or identified. |

16. OTHER INFORMATION

- | | |
|-----------------------|---------------------------------------|
| Contact Point: | Product Safety Manager - 1300-360-732 |
| Prepared by: | Dow Corning Australia Pty Ltd |

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this Company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

(R) indicates Registered Trademark