



TECHNICAL DATA

ROCOL Wire Rope Spray

Wire rope lubricant spray

Description

Rocol Wire Rope Spray is a semi-fluid grease with a combination of lubricating solids and molybdenum disulphide designed for the lubrication and corrosion prevention requirements of wire ropes working under all conditions, including marine environments. Wire Rope Spray penetrates between the strands to the core of the ropes providing complete rope lubrication.

Areas of application

- Wire ropes
- Dock yard cranes
- Cranes
- Chain lifts
- Flying foxes
- Slipways

Features

- Rapidly penetrates wire ropes
- Water repellent
- Anti-wear properties
- High corrosion protection
- Operating temperature range -20°C to +100°C

Directions for use

Shake well before use. Hold upright and spray a thin even coating from a distance of 15 to 30 cm. Test compatibility with painted and coated surfaces, plastics and rubbers, prior to application. Use only as directed.

Technical data

Appearance	Black Liquid Grease
Thickener	Organic Modified Clay
Oil	Solvent Refined Mineral
Lubricating Solids	Molybdenum Disulphide
Drop Point.....	170°C
Penetration (IP132).....	420 to 450
Temperature Range	
Operating	- 20°C to 100°C
Min. Temperature for Application.....	0°C
Pour Point base oil.....	- 10°C
Propellant.....	Hydrocarbon

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is non-hazardous.

Australia

ITW Polymers & Fluids Pty Ltd
100 Hassall Street, Wetherill Park, NSW, 2164
Phone: (02) 9757 8800
Fax: (02) 9757 3855

New Zealand

ITW Polymers & Fluids
18-26 Amelia Earhart Ave, Airport Oaks, Mangere
Phone: 09 256 2122
Fax: 09 256 2124