

MSDS Name HP 250 Q 400 ml Cartridge
 Manufacturer Name ITW Devcon
 Stock No.: 14417
 Kit MSDS Revision Date 1/16/2009

Components :

HP 250 Q Hardener

HP 250 Q Resin

Product Code : 14417

View MSDS : [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#)**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

Product Name: HP 250 Q Resin
 MSDS Manufacturer Number: 0153
 Manufacturer Name: ITW
 Address: 30 Endicott Street
 Danvers, MA 01923
 General Phone Number: (978) 777-1100
 Emergency Phone Number: (800) 424-9300
 CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
 Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)
 MSDS Revision Date: 1/16/2009

HMI S

Health Hazard	2*
Fire Hazard	1
REACTIVITY	1
Personal Protection	X

* Chronic Health Effects:

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Elastomer Modified Diglycidyl Ether	68909-14-8	5 - 10 by weight
Inert material	N/A	10 - 30 by weight
Reaction Product of Epichlorohydrin & Bisphenol A	25085-99-8	10 - 30 by weight
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	10 - 30 by weight
Neopentyl glycol diglycidyl ether	17557-23-2	1 - 5 by weight
Bisphenol A diglycidyl ether resin	25068-38-6	10 - 30 by weight

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Potential Sensitizer Irritant.

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.

Skin:	Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation:	Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
Ingestion:	Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
Chronic Health Effects:	Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
Signs/Symptoms:	Overexposure can cause headaches, dizziness, nausea, and vomiting.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:	> 200° F (93.3° C)
Flash Point Method:	Estimated.
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO ₂) or dry chemical when fighting fires involving this material.
Unsuitable Media:	Water or foam may cause frothing.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization. Heating above 300 deg F in the presence of air may cause slow oxidative decomposition and above 500 deg F may cause polymerization.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.
Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Viscous. Liquid..
Odor:	mild.
Boiling Point:	Not determined.
Melting Point:	Not determined.
Specific Gravity:	1.13

Solubility:	Not determined.
Vapor Density:	> 1 (air = 1)
Vapor Pressure:	Not determined.
Percent Volatile:	0
Evaporation Rate:	Not determined.
pH:	Neutral.
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	> 200° F (93.3° C)
Flash Point Method:	Estimated.
Auto Ignition Temperature:	Not determined.
VOC Content:	0 g/L
Percent Solids by Weight	100

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Heating resin above 300 F in the presence of air may cause slow oxidative decomposition.
Incompatible Materials:	Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines).

SECTION 11 - TOXICOLOGICAL INFORMATION

Neopentyl glycol diglycidyl ether :

Ingestion: Oral - Rat LD50: 4500 mg/kg - [Details of toxic effects not reported other than lethal dose value.] (RTECS)

Bisphenol A diglycidyl ether resin :

Skin: Skin - Rat LD: > 2 gm/kg - [Nutritional and Gross Metabolic - other changes](RTECS)

Ingestion: Oral - Rat LD: > 5 gm/kg - [Nutritional and Gross Metabolic - other changes] (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	No ecotoxicity data was found for the product.
Environmental Fate:	No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal:	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
RCRA Number:	Not determined.

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.
 DOT UN Number: Not applicable.
 DOT Hazard Class: Not applicable.
 DOT Packing Group: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Elastomer Modified Diglycidyl Ether :
 TSCA Inventory Status: Listed
Reaction Product of Epichlorohydrin & Bisphenol A :
 TSCA Inventory Status: Listed
Phenol, polymer with formaldehyde, glycidyl ether :
 TSCA Inventory Status: Listed
Neopentyl glycol diglycidyl ether :
 TSCA Inventory Status: Listed
Bisphenol A diglycidyl ether resin :
 TSCA Inventory Status: Listed
 Canadian Regulations: WHMIS Hazard Class(es): D2B

WHMIS Pictograms



SECTION 16 - ADDITIONAL INFORMATION

HMS Fire Hazard: 1
 HMS Health Hazard: 2*
 HMS Reactivity: 1
 HMS Personal Protection: X
 MSDS Revision Date: 1/16/2009
 MSDS Author: Actio Corporation

Copyright© 1996-2008 [Actio Software Corporation](#). All Rights Reserved.

View MSDS : [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#)

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: HP 250 Q Hardener
 MSDS Manufacturer Number: 0219
 Manufacturer Name: ITW



Address: 30 Endicott Street
Danvers, MA 01923

General Phone Number: (978) 777-1100

Emergency Phone Number: (800) 424-9300

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

MSDS Revision Date: 01/16/2009

Fire Hazard	1
REACTIVITY	1
Personal Protection	X

* Chronic Health Effects:

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Bisphenol A	80-05-7	5 - 10 by weight
Non-hazardous ingredients.	N/A	30 - 60 by weight
Aminoethylpiperazine	140-31-8	10 - 30 by weight
Nonylphenol	25154-52-3	10 - 30 by weight
Inert material	N/A	1 - 5 by weight
Diethylenetriamine	111-40-0	5 - 10 by weight

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:	DANGER! Corrosive. Toxic. Potential Sensitizer Irritant.
Route of Exposure:	Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:	
Eye:	Corrosive. Will cause eye burns, permanent tissue damage, and blindness.
Skin:	Contact causes severe skin irritation and possible burns. may cause permanent skin damage. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation:	May cause severe respiratory system irritation. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
Ingestion:	Harmful if swallowed. Corrosive to the gastrointestinal tract.
Chronic Health Effects:	Prolonged skin contact causes burns. Repeated or prolonged inhalation may cause toxic effects.
Signs/Symptoms:	Depending on solution concentration, material may be corrosive to skin, mucous membranes and eyes. Vapors may cause respiratory irritation.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Other First Aid:

Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties:	Class III B.
Flash Point:	> 200° F (93.3° C)
Flash Point Method:	Estimated.
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO ₂) or dry chemical when fighting fires involving this material.
Unsuitable Media:	Water or foam may cause frothing.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Corrosive. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in section 8.
Personnel Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Avoid contact with eyes and skin. Do not reuse containers without proper cleaning or reconditioning.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Do not store in reactive metal containers. Keep away from acids, oxidizers.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Diethylenetriamine :

Guideline ACGIH: ACGIH TLV-TWA 1 ppm

Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Liquid..
Color:	amber
Odor:	Ammonia like fishy.
Boiling Point:	> 212° F (100° C)
Melting Point:	Not determined.
Specific Gravity:	0.99
Solubility:	> 30%
Vapor Density:	> 1 (air = 1)
Vapor Pressure:	
Percent Volatile:	0
Evaporation Rate:	
pH:	alkaline
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	> 200° F (93.3° C)
Flash Point Method:	Estimated.
Auto Ignition Temperature:	Not determined.
VOC Content:	0 g/L
Percent Solids by Weight	100

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Product may slowly corrode copper, aluminum, zinc and galvanized surfaces.

Incompatible Materials:

Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.

SECTION 11 - TOXICOLOGICAL INFORMATION

Bisphenol A :

Eye: Eye - Rabbit Standard Draize Test. : 250 ug/24H - [severe](RTECS)

Skin: Skin - Rabbit Standard Draize Test. : 500 mg/24H - [mild](RTECS)
 Skin - Rabbit LD50: 3 mL/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)
 Skin - Human TCLo - Lowest published toxic concentration: 1 pph - [Skin and Appendages - dermatitis, allergic (after topical exposure)](RTECS)

Inhalation: Inhalation. - Human TCLo - Lowest published toxic concentration: 20 mg/m³/1H - [Behavioral - headache Gastrointestinal - nausea or vomiting] (RTECS)

Ingestion: Oral - Rat LD50: 1200 mg/kg - [Reproductive - Fertility - female fertility index (e.g. # females pregnant per # sperm positive females; # females pregnant per # females mated)] (RTECS)
 Oral - Mouse LD50: 2400 mg/kg - [Autonomic Nervous System - other (direct) parasympathomimetic oral - convulsions or effect on seizure threshold oral - ataxia] (RTECS)
 Oral - Mouse LD50: 2500 mg/kg - [Details of toxic effects not reported other than lethal dose value.] (RTECS)

Aminoethylpiperazine :

Eye: Eye - Rabbit Standard Draize Test.: 20 mg/24H - [Moderate](RTECS)

Skin: Skin - Rabbit Standard Draize Test.: 5 mg/24H - [severe](RTECS)
 Skin - Rabbit LD50: 880 uL/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)

Ingestion: Oral - Rat LD50: 2140 uL/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)

Nonylphenol :

Skin: Skin - Rabbit Open irritation test -: 500 mg - [Moderate](RTECS)
 Skin - Rabbit LD50: 2140 uL/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)
 Skin - Rabbit LD50: 2140 mg/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)

Ingestion: Oral - Rat LD50: 580 mg/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)
 Oral - Mouse LD50: 1231 mg/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)

Diethylenetriamine :

Skin: Skin - Rabbit Standard Draize Test. : 500 mg(RTECS)
 Skin - Rabbit LD50: 1090 mg/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)
 Skin - Guinea pig LD50: 170 uL/kg - [Details of toxic effects not reported other than lethal dose value.](RTECS)

Inhalation: Inhalation. - Rat LCLo - Lowest published lethal concentration: 70 mg/m³/4H - [Details of toxic effects not reported other than lethal dose value.](RTECS)

Ingestion: Oral - Rat LD50: 1080 mg/kg - [oral - convulsions or effect on seizure threshold] (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

RCRA Number:

D002

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Corrosive liquid, basic, organic, n.o.s. (N-Aminoethylpiperazine, Nonylphenol) Marine Pollutant (Nonylphenol)

DOT UN Number: 3267

DOT Hazard Class: 8

DOT Packing Group: III

DOT Exemption: ORM-D Small quantity exemption

SECTION 15 - REGULATORY INFORMATION

Bisphenol A :

TSCA Inventory Status: Listed

SARA: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

State Regulations: Listed in the State of Massachusetts Hazardous Substance List.
Listed in the New Jersey State Right to Know List.
Listed in the Pennsylvania State Hazardous Substances List.

Aminoethylpiperazine :

TSCA Inventory Status: Listed

State Regulations: Listed in the State of Massachusetts Hazardous Substance List.
Listed in the Pennsylvania State Hazardous Substances List.

Nonylphenol :

TSCA Inventory Status: Listed

State Regulations: Listed in the State of Massachusetts Hazardous Substance List.
Listed in the Pennsylvania State Hazardous Substances List.

Diethylenetriamine :

TSCA Inventory Status: Listed

State Regulations: Listed in the State of Massachusetts Hazardous Substance List.
Listed in the Pennsylvania State Hazardous Substances List.

Canadian Regulations.

WHMIS Hazard Class(es): E; D2B
All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms



SECTION 16 - ADDITIONAL INFORMATION

HMIS Fire Hazard: 1

HMIS Health Hazard: 3*

HMIS Reactivity: 1

HMIS Personal Protection: X

MSDS Revision Date: 01/16/2009

MSDS Author: Actio Corporation

