



# MATERIAL SAFETY DATA SHEET

PRODUCT NAME **808 SILICONE SPRAY**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier Name** CRC INDUSTRIES (AUST) PTY LIMITED  
**Address** 9 Gladstone Road, Castle Hill, NSW, AUSTRALIA, 2154  
**Telephone** (02) 9849 6700  
**Fax** (02) 9680 4914  
**Emergency** 131 126  
**Email** info@crcind.com.au  
**Web Site** http://www.crcind.com.au/  
**Synonym(s)** CRC SILICONE 808 • CRC 808 SILICONE • 3055 - PRODUCT CODE • 808 SILICONE (AEROSOL)  
**Use(s)** LUBRICANT • SILICONE LUBRICANT  
**MSDS Date** 01 January 2006

## 2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

<b>UN No.</b>	1950	<b>DG Class</b>	2.1	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Pkg Group</b>	None Allocated	<b>Hazchem Code</b>	2Y	<b>EPG</b>	2D1

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
LIQUEFIED PETROLEUM GAS (LPG)	C3H8/C3H6/C4H10	68476-85-7	30-60%
ALIPHATIC HYDROCARBON(S)	Not Available	6943-35-9	10-30%
POLYDIMETHYLSILOXANE	Not Available	Not Available	10-30%

## 4. FIRST AID MEASURES

**Eye** If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poison Information Centre or a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

**Advice to Doctor** Treat symptomatically

# PRODUCT NAME 808 SILICONE SPRAY

## 5. FIRE FIGHTING MEASURES

<b>Flammability</b>	Highly flammable aerosol. May evolve toxic gases (eg: carbon oxides, hydrocarbons) when heated to decomposition. Vapours may form explosive mixtures in air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights etc. when handling. Aerosol containers may explode when heated to temperatures above 50°C.
<b>Fire and Explosion</b>	Highly flammable - explosive vapour. Evacuate area & contact emergency services. Toxic gases (carbon oxides, hydrocarbons) may be evolved when heated. Remain upwind and notify those downwind of hazard. Wear full protective equipment (see spill above) including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
<b>Extinguishing</b>	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
<b>Hazchem Code</b>	2Y

## 6. ACCIDENTAL RELEASE MEASURES

<b>Spillage</b>	If aerosol can damaged/leaking, ventilate and clear area of all unprotected personnel. Wear splash-proof goggles, PVC/rubber gloves, a Type A-Class P1 (Organic vapour and Particulate) respirator (where an inhalation risk exists) and coveralls. Collect and allow to discharge outdoors. Absorb residues with sand or similar and place in clean containers for disposal.
-----------------	---

## 7. STORAGE AND HANDLING

<b>Storage</b>	Store in cool, dry, well ventilated area, removed from direct sunlight, heat & ignition sources, oxidising agents, acids, alkalis & foodstuffs. Ensure aerosol containers are adequately labelled, protected from physical damage and sealed when not in use. Inspect regularly for damaged/ leaking containers. Large storage areas should have appropriate fire protection and ventilation systems.
<b>Handling</b>	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
	LIQUEFIED PETROLEUM GAS (LPG)	NOHSC (AUS)	1000.0	1800.0	1000.0	1800.0

<b>Biological Limits</b>	No biological limit allocated.
<b>Engineering Controls</b>	Do not inhale vapours. Use in well ventilated areas. In poorly ventilated areas, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.
<b>PPE</b>	Wear splash-proof goggles and safety glasses. When using large quantities or where heavy contamination is likely, wear rubber or PVC gloves and coveralls. Where an inhalation risk exists, wear a Type A-Class P1 (Organic gases/vapours and Particulate) Respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	CLEAR COLOURLESS LIQUID (AEROSOL DISPENSED)	<b>Solubility (water)</b>	INSOLUBLE
<b>Odour</b>	ETHERAL/SOLVENT ODOUR	<b>Specific Gravity</b>	0.87
<b>pH</b>	NOT RELEVANT	<b>% Volatiles</b>	60%
<b>Vapour Pressure</b>	NOT AVAILABLE	<b>Flammability</b>	HIGHLY FLAMMABLE
<b>Vapour Density</b>	> 1 (Air = 1)	<b>Flash Point</b>	-17°C

## PRODUCT NAME 808 SILICONE SPRAY

<b>Boiling Point</b>	80°C (Initial)	<b>Upper Explosion Limit</b>	7.4 %
<b>Melting Point</b>	NOT AVAILABLE	<b>Lower Explosion Limit</b>	1.2 %
<b>Evaporation Rate</b>	NOT AVAILABLE	<b>Autoignition Temperature</b>	550°C

### 10. STABILITY AND REACTIVITY

<b>Material to Avoid</b>	Incompatible with oxidising agents (eg. hypochlorites, peroxides), acids (eg. sulphuric acid), strong alkalis (eg. hydroxides), heat and ignition sources.
<b>Decomposition</b>	May evolve toxic gases (eg: carbon oxides, hydrocarbons) when heated to decomposition.

### 11. TOXICOLOGICAL INFORMATION

<b>Health Hazard Summary</b>	Low to moderate toxicity - irritant. This product may only have the potential to cause adverse health effects if intentionally misused (eg. deliberately inhaling contents). Over exposure may result in adverse effects to the central nervous system. Use safe work practices to avoid eye or skin contact and vapour inhalation.
<b>Eye</b>	Irritant. Contact may result in irritation, lacrimation, pain and redness.
<b>Inhalation</b>	Irritant. Inhalation may cause irritation to the respiratory system, nose and throat irritation, coughing, and headache. Over exposure may result in nausea, dizziness and drowsiness.
<b>Skin</b>	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis.
<b>Ingestion</b>	Low to moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain and drowsiness with large quantities. Aspiration may result in chemical pneumonitis and pulmonary oedema. Ingestion is considered unlikely due to product form.
<b>Toxicity Data</b>	No LD50 data available for this product.

### 12. ECOLOGICAL INFORMATION

<b>Environment</b>	Aliphatic hydrocarbons behave differently in the environment depending on their size. WATER: Light aliphatics volatilise rapidly from water (half life - few hours). Bioconcentration should not be significant. SOIL: Light aliphatics biodegrade quickly in soil and water, heavy aliphatics biodegrade very slowly. ATMOSPHERE: Vapour-phase aliphatics will degrade by reaction with hydroxyl radicals.
--------------------	---

### 13. DISPOSAL CONSIDERATIONS

<b>Waste Disposal</b>	For small amounts absorb contents with sand or similar and dispose of to an approved landfill site. Do not puncture or incinerate aerosol cans. Contact the manufacturer for additional information.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

### 14. TRANSPORT INFORMATION



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

<b>Shipping Name</b>	AEROSOLS				
<b>UN No.</b>	1950	<b>DG Class</b>	2.1	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Pkg Group</b>	None Allocated	<b>Hazchem Code</b>	2Y	<b>EPG</b>	2D1

### 15. REGULATORY INFORMATION

<b>Poison Schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
<b>AICS</b>	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

### 16. OTHER INFORMATION

<b>Additional</b>	AEROSOL CANS may explode at temperatures approaching 50°C.
-------------------	--

# PRODUCT NAME **808 SILICONE SPRAY**

## Information

### ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

## Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ('MSDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.

## Prepared By

Risk Management Technologies

5 Ventnor Ave, West Perth

Western Australia 6005

Phone: +61 8 9322 1711

Fax: +61 8 9322 1794

Email: info@rmt.com.au

Web: www.rmt.com.au

**MSDS Date:** 01 January 2006

**End of Report**