



MATERIAL SAFETY DATA SHEET

PRODUCT NAME **CRC 5045 SO EASY**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name CRC INDUSTRIES (AUST) PTY LIMITED
Address 9 Gladstone Road, Castle Hill, NSW, AUSTRALIA, 2154
Telephone (02) 9849 6700
Fax (02) 9680 4914
Emergency 131 126
Email info@crcind.com.au
Web Site http://www.crcind.com.au/
Synonym(s) 5045 - PRODUCT CODE • SO EASY
Use(s) PROTECTANT • PROTECTIVE COATING
MSDS Date 01 July 2008

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	1950	DG Class	2.1	Subsidiary Risk(s)	None Allocated
Pkg Group	None Allocated	Hazchem Code	2Y	EPG	2D1

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
LIQUEFIED PETROLEUM GAS (LPG)	C3H8/C3H6/C4H10	68476-85-7	10-30%
WATER	H2O	7732-18-5	>60%
SILICONE	Not Available	Not Available	10-30%
SURFACTANT(S)	Not Available	Not Available	1-10%
PRESERVATIVE	Not Available	Not Available	<1%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poison Information Centre or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

Advice to Doctor Treat symptomatically

First Aid Facilities Eye wash facilities and safety shower are recommended.

5. FIRE FIGHTING MEASURES

Flammability	Flammable liquid/ aerosol. Vapours may form explosive mixtures with air. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol cans may explode if heated. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights etc. when handling. Aerosol cans may explode when heated to temperatures > 50°C.
Fire and Explosion	Flammable liquid - explosive aerosol. Evacuate area and contact emergency services. Toxic gases (hydrocarbons, carbon oxides) may be evolved when heated. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
Hazchem Code	2Y

6. ACCIDENTAL RELEASE MEASURES

Spillage	If can is punctured, clear area of all unprotected personnel and ventilate area (if in confined area). Wearing splash-proof goggles, PVC/rubber gloves and coveralls, collect and allow to discharge outdoors. If discharge occurs in confined or poorly ventilated area, a Type A-Class P1 (Organic vapour and Particulate) respirator is required. Absorb residues with sand or similar and place in clean containers for disposal.
-----------------	---

7. STORAGE AND HANDLING

Storage	Store in cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, direct sunlight, heat or ignition sources, foodstuffs, out of direct sunlight and out of the reach of children. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	LIQUEFIED PETROLEUM GAS (LPG)	NOHSC (AUS)	1000.0	1800.0	1000.0	1800.0

Biological Limits	No biological limit allocated.
Engineering Controls	Do not inhale vapours. Use in well ventilated areas. In poorly ventilated areas, mechanical explosion proof extraction ventilation is recommended. Flammable/ explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.
PPE	Wear splash-proof goggles and safety glasses. When using large quantities or where heavy contamination is likely, wear rubber or PVC gloves, coveralls and safety glasses.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	DENSE WHITE FOAM (AEROSOL DISPENSED)	Solubility (water)	SOLUBLE
Odour	SLIGHT ODOUR	Specific Gravity	0.99
pH	NOT AVAILABLE	% Volatiles	93 %
Vapour Pressure	18 mm Hg @ 20°C	Flammability	FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT AVAILABLE
Boiling Point	100°C	Upper Explosion Limit	NOT AVAILABLE

PRODUCT NAME CRC 5045 SO EASY

Melting Point	0°C	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	AS FOR WATER	Autoignition Temperature	NOT AVAILABLE

10. STABILITY AND REACTIVITY

Material to Avoid Incompatible with oxidising agents (eg. hypochlorites, peroxides), acids (eg. sulphuric acid), strong alkalis (eg. hydroxides), heat and ignition sources.

Decomposition May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Low toxicity. This product can be fatal if contents are deliberately concentrated and inhaled. Use safe work practices to avoid prolonged eye or skin contact and vapour inhalation at high levels in poorly ventilated areas.

Eye Low irritant. Contact may result in irritation and lacrimation.

Inhalation Irritant. Inhalation may cause irritation to the respiratory system, nose and throat irritation, coughing, and headache. Over exposure may result in nausea, dizziness and drowsiness.

Skin Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.

Ingestion Low toxicity. Ingestion may result in gastrointestinal irritation, nausea and vomiting. However, due to product form ingestion is considered unlikely.

Toxicity Data No LD50 data available for this product.

12. ECOLOGICAL INFORMATION

Environment Hydrocarbon propellants will quickly evaporate from soil or water and enter the atmosphere. In the atmosphere propellants are expected to exist entirely in the vapour phase and will react with hydroxyl radicals. Estimated half lives vary from 6 days (butane) to 13 days (propane). Hydrocarbon propellants are not ozone depleting.

13. DISPOSAL CONSIDERATIONS

Waste Disposal For small amounts absorb contents with sand or similar and dispose of to an approved landfill site. Do not puncture or incinerate aerosol cans. Contact the manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	AEROSOLS				
UN No.	1950	DG Class	2.1	Subsidiary Risk(s)	None Allocated
Pkg Group	None Allocated	Hazchem Code	2Y	EPG	2D1
IATA					
Shipping Name	AEROSOLS				
UN No.	1950	DG Class	2.1	Subsidiary Risk(s)	None Allocated
Pkg Group	None Allocated				
IMDG					
Shipping Name	AEROSOLS				
UN No.	1950	DG Class	2.1	Subsidiary Risk(s)	None Allocated
Pkg Group	None Allocated				

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWAVES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ('MSDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

PRODUCT NAME **CRC 5045 SO EASY**

MSDS Date:01 July 2008

End of Report

CHEM ALERT

Page 5 of 5
RMT
Reviewed: 01 Jul 2008
Printed: 17 Jul 2008