

hose reels - metal

enclosed metal hose reels

Each reel's rugged metal casing protects the hose and adds years to its operating life in even the busiest of industrial workplaces. Its slim design is also a space saver, especially for multiple reel installations. These spring rewind reels are available in air/water, oil and grease models.

Features

- Versatile surface, ceiling or wall mounted units
- External swivel for easy maintenance
- 180° hose rotation (except EMA1015)
- Made from powdered coated steel with four bolt steel mounting plate
- 5 year warranty
- 10 year parts guarantee

*Macnaught can produce metal reels to suit your specific requirements. Minimum order quantities apply.



EMA1015

Model	Description	Hose ID	Hose Length	Working Pressure	Max Op Temp	Reel Inlet	Hose Outlet
EMA1015	Air/Water	10 mm (3/8")	15 m	3000 kPa (430 psi)	80°C	3/8" BSP	3/8" BSP
EMA1210	Air/Water	12 mm (1/2")	10 m	3000 kPa (430 psi)	80°C	1/2" BSP	1/2" BSP
EMG0615	Grease	6 mm (1/4")	15 m	34 500 kPa (5000 psi)	100°C	1/4" BSP	1/4" BSP
EMO1210	Oil	12 mm (1/2")	10 m	13 800 kPa (2000 psi)	100°C	1/2" BSP	1/2" BSP