

greasing equipment - air operated

powerlube®

P3

The P3 POWERLUBE® is the ultimate in high pressure, air-powered greasing. With models available to suit containers from 12.5kg (28 lbs.) to 22 kg (48 lbs.), it is fitted with a 50:1 ratio air motor which can run off most small compressors to provide fast, continuous greasing.

Features

- quiet, non-corroding air motor
- low air consumption
- no air line lubricator required
- rubber edged follower plate
- 4m (13 ft.) x 6 mm (1/4") ID delivery hose
- B2 booster gun with 360° ZSB swivel
- fully serviceable
- 10 year warranty and parts guarantee

Specifications

- grease viscosity: up to NLGI No.2
- wetted components: zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber
- output: approx. 460 g/min (16 oz/min)
- max. air pressure: 1 030 kPa (150 psi, 10.3 bar)
- min. air pressure: 400 kPa (60 psi, 4 bar)
- min. compressor size: 0.08 m³/min (3 cfm)
- air inlet/fluid outlet: 1/4" NPT (F)
- pump ratio: 50:1 (grease pressure is 50 times air)
- B2 gun pressure: up to 69 000 kPa (10 000 psi, 690 bar) (boost pressure)
- hose thread: 1/4" NPT (M)



Accessories

- TR5 Trolley
- PDF13 Push On Extension
- PDF21 Push On Extension
- TA-7K Filter & Regulator Kit
- KZDXL Straight Needlepoint Coupler
- KRV Pressure Release Valve

