

dispensing equipment - oil control guns

electronic oil control gun

MH50R Electronic Display with Rigid Extension
MH50F Electronic Display with Flexible Extension

Features

- robust aluminium handle with trigger guard
- easy to read and resettable 6-digit LC display
- reset batch total and non-reset total display options
- sleep mode (2 minute idle limit) to preserve battery life
- oval gear mechanism for optimum accuracy
- protective shroud on meter
- automatic non-drip nozzle
- shock resistant
- fully serviceable
- 10 year warranty and parts guarantee

Specifications

- | | |
|--------------------------|-----------------------------------------------------------------------------------------------|
| • compatible fluids: | lubricating oils up to SAE 140, automatic transmission fluid and anti-freeze/anti-boil |
| • wetted components: | acetal, aluminium, nitrile (NBR), steel |
| • accuracy | ±0.5% of reading (lubricating oils) |
| • flow range: | 1-30 L/min (0.26 - 8 US gal/min) |
| • pressure loss: | 100 kPa (14.4 psi, 1 bar) @ 12 L/min (3.2 US gal/min) (without nozzle) with calibration fluid |
| • max. pressure: | 10 350 kPa (1500 psi , 103.5 Bar) |
| • inlet swivel: | ½" BSPT or NPT (F) |
| • operating temperature: | -10°C (14°F) to 55°C (131°F) |
| • weight: | 1.3kg (2.8lbs) |
| • battery: | 2 x 1.5 volt alkaline AAA |

Accessories

- IM Range Coloured Shrouds



MH50R

