

accessories

TB23S suction tube

This is the NPT version of the TB17S.




TB25S suction tube

A suction tube suitable for use with the pump models T112, T312, T512, R500S (stub) oil pumps in drums and tanks to 1200 mm deep. 1" UNF (M) thread.



TB26S suction tube

This suction tube has the same features as the TB25S, but has a foot valve included for when improved priming is required.



TD42S suction tube

A suction tube suitable for use with the R300S and R1000S (stub) oil pumps in drums and tanks to 1200 mm deep. Complete with 3/4" BSP fixing adaptor.



TB24S suction tube

This is the NPT version of the TD42S.



oil feeder hoses

TB-20K

A 3 m (10 ft) high-pressure feeder hose suitable for use with the T512 OILMASTER® pump. The hose has an I.D. of 12.5 mm (1/2") and a working pressure of 6 900 kPa (1 000psi, 69 bar).



TD-25K

This 3 m (10 ft) low pressure feeder hose is ideal for use with the R300 ratio oil pump, and the T312 OILMASTER® pump. The hose has an I.D. of 12.5 mm (1/2") and a working pressure of 2 800 kPa (400 psi, 28 bar).



fuel filters

GB fuel filter (10 µm)

GB fuel filter (10 µm)
Supplied with fittings to suit the GP RAPIDFLO™ pump.
Inlet: 1" NPT Outlet: 1" hoesetail



HA fuel filter (10 µm)

Supplied with fittings to suit the HP LITRESTROKE™ pump.
Inlet: 1" NPT Outlet: 1" hoesetail



VA fuel filter (10 µm)

Supplied with fittings to suit the PVRH pump.
Inlet: 1" NPT
Outlet : 3/4" hoesetail



HA1S fuel filter (10 µm)

Inlet thread: 1" NPT
Outlet thread: 1" NPT



HA7S filter element (10 µm)

The 10 µm filter element used in the GB, HA and VA fuel filters. Supplied with seals.

